

FTTH FIELD INSTALLATION CONNECTOR



Field Assembly Connector (Fast Connector) adopts the newest fiber terminal technology, the optical and mechanical properties are all up to the standard jump cable, it provides powerful technical support for FTTH access.

FEATURES / MATERIAL

- Field installable, high reliability.
- Fiber pre-installed, no polishing required.
- Compact size, light weight.
- Suitable for drop cable and pigtail to home.



UFH3011




UFH3012

Part Number	Description	Color
UFH3011	SC/UPC Field Install Connector, for Flat Cable	Blue
UFH3012	SC/APC Field Install Connector, for Flat Cable	Green


FTTH SMART OUTLET

FEATURES / MATERIAL

- ABS material used ensures the body strong and light
- Easy installations : Mount on wall
- Splicing tray can be removed when needed or during the installation for the convenient operation and installation
- Double-layer design for easier installation and maintenances
 - Upper layer for splicing.
 - Lower layer for distribution.
- Without adapter
- Suitable for SC & LC adapter



UF-1014



UF-1002



UFH3022



UFH3026

Part Number	Description	Dimension H x W x D(mm)	Color
UF-1002	2 Port Duplex Home Fiber Termination Box w/o adapter, 4 Fiber, empty	140 x 90 x 20.5	Light Grey
UF-1014	4 Port Simplex Fiber Termination Box w/o adapter, 4 Fiber, empty	120 x 80 x 25	Light Grey
UFH3022	FTTH Smart Housing Outlet for 2 x SC Simplex (or LC Duplex), empty	130 x 84 x 24	White
UFH3026	Mini FTTH Smart Housing Outlet for 2 x SC Simplex (or LC Duplex), empty	85 x 85 x 25	White

FTTH ROUND CABLE ASSEMBLY

FEATURES / CONSTRUCTION

- It is a finished cable from factory
- Which is easily to installation
- Optical Fiber can be ITU-T G.657A2 and fully compatible ITU-T G.652
- Simple structure, light weight and practical
- Safe and environment friendly with FR-LSZH jacket
- Included protector sleeve, heatshiink tube & cable ties



UFP966542-03-OI

Part Number	Description
UFP966542-03-OI	OFTK SC (APC) OUTDOOR / INDOOR PATCH CORD, 3 M, LSZH, OD .35 mm.

FTTH FLAT CABLE ASSEMBLY

FEATURES / CONSTRUCTION

- It is a finished cable from factory
- Which is easily to installation
- Optical Fiber can be ITU-T G.657A2 and fully compatible ITU-T G.652
- Simple structure, light weight and practical
- Two Metallic strength member protects the fiber with tensile strength
- With solid messenger wire (1.2mm.)
- Safe and environment friendly with FR-LSZH jacket
- Available length 25, 50, 75, 100, 125, 150, 175, 200, 225, 250, 275 and 300 m.



UFH9862-XXX

Part Number	Description
UFH9862-XXX-TCC	FTTH Flat Cable Assembly XXX M. , LSZH SC/APC to SC/APC

XXX = length ; 025(25 m.), 300(300 m.)