

WS28 Metal Connector

P/N	Product Figure	Dimension	Matching
TQM			
TQF			
ZQF			
ZZF			
ZMZ			

WS28, WF28, WY28	2	3	4	7	8	9	10	10B	12	16	17	20	24	26
公端绝缘体正面图 Male contact face view														
额定电流 (A) Rated current (A)	50	50	25	25	25	25.5	25	10	10	10	10	5	5	5
接触件直径(mm) Contact diameter(mm)	φ3.5X2	φ3.5X3	φ2.5X4	φ2.5X7	φ2.5X8	φ2.5X9	φ2.5X10	φ1.5X10	φ1.5X12	φ1.5X16	φ1.5X17	φ1X20	φ1X24	φ1X26
工作电压 (AC,V) Rated voltage (AC,V)	500	500	500	500	500	500	500	500	500	500	500	400	400	400
耐压 (AC,V) 1 min Test voltage (AC,V) 1 min	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1200	1200	1200
接触电阻 (mΩ) Contact resistance (mΩ)	0.5	0.5	1	1	1	1.5	1	2.5	2.5	2.5	2.5	5	5	5
绝缘电阻 (MΩ) Insulation resistance (MΩ)	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
线规 (mm²/AWG) Wire size (mm²/AWG)	≤10/7	≤10/7	≤4/11	≤4/11	≤4/11	≤4/11	≤4/11	≤2/14	≤2/14	≤2/14	≤2/14	≤0.75/18	≤0.75/18	≤0.75/18