

UT136+



Specifications	Range	UT136B+	UT136C+
DC voltage (V)	1000V	±(0.7%+3)	±(0.7%+3)
AC voltage (V)	1000V	±(1%+3)	±(1%+3)
DC current (A)	10A	±(1%+3)	±(1%+3)
AC current (A)	10A	±(1.2%+5)	±(1.2%+5)
Resistance (Ω)	40MΩ	±(0.8%+2)	±(0.8%+2)
Capacitance (F)	40mF	±(3%+5)	±(3%+5)
Frequency (Hz)	400Hz~40mHz	±(0.1%+4)	±(0.1%+4)
Temperature (°C)	-40~1000°C		±(1%+4)
Temperature (°F)	-40~1832°F		±(1.5%+5)
Features			
Display count		4000	4000
hFE	Transistor measurement	√	√
NCV	Non-contact voltage detection	√	
Diode/transistor		√	√
Continuity buzzer		√	√
Data hold/Auto power off		√	√
Low battery/Indication		√	√
LCD backlight		√	√
Safety rating	CAT II 1000V, CAT III 600V	√	√
Drop test	2m	√	√
General Characteristics			
Power	1.5V battery (R6) x 2		
Display	56.5mm x 36mm		
Product color	Red and grey		
Product net weight	330g		
Product size	175mm x 83mm x 53mm		
Standard accessories	Batteries, test leads, temperature probe (UT136C+)		
Standard individual packing	Gift Box, English manual		
Standard quantity per carton	30pcs		
Standard carton measurement	390mm x 335mm x 340mm		
Standard carton gross weight	12.75kg		