UT210D/210E

Specifications	Range	Best Accuracy	
Model		**UT210D**	**UT210E**
AC Current (A)	20A/200A	±(2.5%+8)	
	2A/20A/100A		±(2.5%+5)
DC Current (A)	20A/200A	±(2%+3)	
	2A/20A/100A		±(2%+3)
AC Voltage (V)	2V/20V/200V/600V	±(1%+3)	±(1%+3)
DC Voltage (V)	200mV/2V/20V/200V/600V	±(0.7%+3)	±(0.7%+3)
Resistance (Ω)	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1%+2)	±(1%+2)
Frequency	10Hz/100Hz/1kHz/10kHz/60kHz	±(0.1%+4)	
Capacitance (F)	2nF/20nF/200nF/2μF /20μF/200μF/2mF/20mF	±(4%+5)	±(4%+5)
Temperature (℃)	-40~1000℃	±(1%+3)	
Temperature (℉)	-40~1832℉	±(1.5%+5)	

UT210D/210E

Features			
Display Count		2000	2000
Auto Range		√	√
Jaw Capacity		17mm	17mm
True RMS		√	√
Diode	Around 3.0V	√	√
V.F.C.			√
NCV		√	√
Auto Power Off	Around 15 minutes	√	√
Continuity Buzzer		√	√
Low Battery Indication	≤2.5V	√	√
Data Hold		√	√
Zero Mode		√	√
MAX/MIN		√	√
LCD Backlight		√	√
Input Protection		√	√
Input Impedance for DCV	≥10MΩ	√	√

UT210D/210E

General Characteristics	
Power	AAA 1.5V x 2
LCD Size	39.3mm x 26.5mm
Product Color	Red and grey
Product Net Weight	170g
Product Size	175mm x 60mm x 33.5mm
Standard Accessories	UT210D - Batteries, Test Lead, Point Contact Temperature Probe
	UT210E - Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying bag, English Manual
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	385mm x 345mm x 305mm (0.041 CBM Per Standard Carton)
Standard Carton Gross Weight	11kg