UT601/602/603

Specifications	Range	Best Accuracy		
Model		**UT601**	**UT602**	**UT603**
Resistance (Ω)	20Ω/200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ/200MΩ/2000MΩ	±(0.8%+1)		
	20Ω/200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ/2000MΩ		±(0.8%+1)	
	200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ			±(0.8%+1)
Capacitance (C)	200pF/2nF/20nF/200nF/2uF/20uF/200uF/2mF/20mF	±(0.5%+10)		
	2nF/20nF/200nF/2uF/20uF/200uF/600uF			±(1%+5)
Inductance (H)	2mH/20mH/200mH/2H/20H/200H		±(2%+8)	
	2mH/20mH/200mH/2H/20H			±(2%+8)
Features				
Max Display		1999	1999	1999
Manual Range		√	√	√
Diode		√	√	√
Transistor		√	√	√
Continuity Buzzer		√	√	√
Low Battery Indication		√	√	√
Data Hold			√	

General Characteristics	
Power	9V Battery (6F22)
LCD Size	61mm X 32mm
Product Color	Red and Grey
Product Net Weight	**UT601/UT602**-310g,**UT603**-312g
Product Size	172mm X 83mm X38mm
Standard Accessories	Battery, Test Clip, Holster
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598mm X 418mm X 340mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	21kg